

# PolyKar<sup>®</sup> BEZBARVÝ LAK

Clear coat, category : Sprays

**DESCRIPTION AND USAGE**

PolyKar BEZBARVÝ LAK is fast drying paint with excellent gloss and good resistance against chemicals. It is used to get higher gloss both by painted and non-painted pieces. It is suitable for metal and some plastic parts on automobile body, generally on metal and wood.

**ENVIRONMENT**

PolyKar BEZBARVÝ LAK must not be used for filling places which are in direct contact with food and drinking water.

**APPLICATION**

Before application the surface must be dry, without dust, grease and remain of corrosion. Very gloss surfaces must be roughened with sanding paper. Content in the can must be shaken well at least for two minutes before usage, to obtain an uniform diffusion of pigments in paint. Surrounding surface must be covered with paper or masking tape to avoid its pollution.

Ideal temperature for application is between 20 – 25°C, ideal conditions are out of direct solar radiation and in windlessness. It is suitable to test the application on adjacent surface to check the truth of colour tint. It is applied by cross strokes in thin layers in distance circa 25 cm – first horizontally, then vertically. It is necessary to wait between application of each layer for 2 – 3 minutes.

Warning: In case of application of preparation on old coatings based on synthetic resins it can get to crumpling or flaking of the paint.

**DRYING**

At temperature 20°C two layers of preparation applied by cross strokes are dry after 5 - 10 minutes on dust, after 30 – 40 minutes for manipulation and after 12 hours absolutely hardened. Interval for application of further layers is not restricted.

**TOOLS CLEANING**

Dirty parts of tools can be cleaned with white spirit. After finishing of work it is necessary to turn the can upside-down and clean the nozzle and valve by short pressing. Confined nozzle can be cleaned in thinner.

**STORAGE AND PACKAGING**

It is necessary to ensure the temperature +5°C - +25°C and avoid direct solar radiation during storage and transport. Store in dry and cold place. We guarantee shelf life and quality of the product for 5 years.

Packaging:  
- 500 ml – spray

**COLOUR**

Transparent

**BKP GROUP, a. s.**