

PolyKar[®] UBS

Overpaintable protective spray coating, category : Protective coatings

DESCRIPTION AND USAGE

PolyKar UBS, preparation for protection of car body, is made on the base of synthetic resins. It forms thick elastic layer resistant against strokes of small stones. It protect against corrosion, petrol, oils, water and salt. It has protective and damping properties. Overpaintable.

SURFACE	ADHESION
Metal	++
Steel, aluminum	++
Polyester putties BKP	++
Polyester fibreglass	++
Reactive primers	++
Plastics	++

++ excellent / + good / o satisfactory /- not satisfactory

ENVIRONMENT

The preparation must not be used for filling places which are in direct contact with food and drinking water.

APPLICATION

The surface must be clean and dry before application. Places, which are not intended to be terated by the preparation, must be covered. PolyKar UBS is applied by spray gun. We recommend to use nozzle 4 mm, pressure 0,2 – 0,4 MPa.

It is applied in 2 or 3 layers, it is necessary to wait 5 minutes between the application of each layer. At temperature 20°C the preparation is dry after 40 – 60 minutes.

1 liter of preparation covers about 3,5 m² in thickness of layer 100 µm.

Content in the can must be shaken well before usage!!!

TOOLS CLEANING

Dirty parts of tools can be cleaned with white spirit or similar solvent. Only non-hardened preparation can be cleaned.

STORAGE AND PACKAGING

It is necessary to ensure the temperature from +5 °C to 25°C and avoid direct solar radiation during storage and transport. Store in dry and cold place. We guarantee shelf life and quality of the product for 24 months.

Packaging:

- 1 l – cartouche to spraygun
- 1,5 l – cartouche to spraygun
- 3,75 l – can (application by brush)

COLOUR

Black, grey, white