

PolyKar[®] ZÁKLAD NA PLASTY

Primer for plastic parts, category : Sprays

DESCRIPTION AND USAGE

PolyKar ZÁKLAD NA PLASTY is based on special polymers which increase the adhesion of upper coatings on plastics (interceptors, spring-back mirrors, plinths etc.). Slight pigmentation gives a control, if the preparation had been applied on all places, which are intended to be coated.

ENVIRONMENT

PolyKar ZÁKLAD NA PLASTY must not be used for filling places which are in direct contact with food and drinking water.

APPLICATION

Before application the surface must be dry, without dust, grease and remain of corrosion. Very gloss surfaces must be roughened with sanding paper. Content in the can must be shaken well at least for two minutes before usage, to obtain an uniform diffusion of pigments in paint. Surrounding surface must be covered with paper or masking tape to avoid its pollution.

Ideal temperature for application is between 20 – 25°C, ideal conditions are out of direct solar radiation and in windlessness. It is suitable to test the application on adjacent surface. It is applied by cross strokes in thin layers in distance circa 25 cm – first horizontally, then vertically.

Warning: In case of application of preparation on old coatings based on synthetic resins it can get to crumpling or flaking of the paint. Some plastics can not be overpainted neither with application of plastic primer.

DRYING

At temperature 20°C one layer (in thickness 3 – 5 µm) of preparation applied by cross strokes is dry after 15 minutes on dust and after 30 – 40 minutes for manipulation. Interval for application of further layers and overpainting with other paints is 15 minutes.

TOOLS CLEANING

Dirty parts of tools can be cleaned with white spirit. After finishing of work it is necessary to turn the can upside-down and clean the nozzle and valve by short pressing. Confined nozzle can be cleaned in thinner.

STORAGE AND PACKAGING

It is necessary to ensure the temperature +5°C - +25°C and avoid direct solar radiation during storage and transport. Store in dry and cold place. We guarantee shelf life and quality of the product for 5 years.

Packaging:
- 400 ml – spray

COLOUR

Transparent

BKP GROUP, a. s.