

PolyKar[®] ČERNÝ MAT

Acrylic paint, category : Sprays

DESCRIPTION AND USAGE

PolyKar ČERNÝ MAT is fast drying paint suitable for universal usage. It can be applied on car parts made from metal, sheet metal and plastics (after application of plastic primer) and can be used also as covering coating for various paint works both in exterior and interior. It has good spill, spreading rate and adhesion, resistance against light and weather conditions. It is resistant against scratching.

ENVIRONMENT

PolyKar ČERNÝ MAT must not be used for filling places which are in direct contact with food and drinking water.

APPLICATION

Before application the surface must be dry, without dust, grease and remain of corrosion. Very gloss surfaces must be roughened with sanding paper. Content in the can must be shaken well at least for two minutes before usage, to obtain an uniform diffusion of pigments in paint. Surrounding surface must be covered with paper or masking tape to avoid its pollution.

Ideal temperature for application is between 20 – 25°C, ideal conditions are out of direct solar radiation and in windlessness. It is suitable to test the application on adjacent surface to check the truth of colour tint. It is applied by cross strokes in thin layers in distance circa 25 cm – first horizontally, then vertically. It is necessary to wait between application of each layer for 2 – 3 minutes.

Warning: In case of application of preparation on old coatings based on synthetic resins it can get to crumpling or flaking of the paint.

DRYING

At temperature 20°C two layers of preparation applied by cross strokes are dry after 20 minutes on dust and after 12 hours absolutely hardened. Interval for application of further layers is not restricted.

TOOLS CLEANING

Dirty parts of tools can be cleaned with white spirit. After finishing of work it is necessary to turn the can upside-down and clean the nozzle and valve by short pressing. Confined nozzle can be cleaned in thinner.

STORAGE AND PACKAGING

It is necessary to ensure the temperature 20°C and avoid direct solar radiation during storage and transport. Store in dry and cold place. We guarantee shelf life and quality of the product for 5 years.

Packaging:

- 500 ml – spray

COLOUR

Black

BKP GROUP, a. s.