

PolyKar[®] BITUMEN

Non-overpaintable protective coating, category : Sprays

DESCRIPTION AND USAGE

PolyKar BITUMEN, preparation for protection of car cassis, semi-trailers, ships and metal products, is made on the base of rubber and asphalt. It forms resistant elastic layer protecting against the abrasive treatment of spreading, corrosion, petrol, oils, water and salt. Its function is also the sound protection. It has excellent adhesion to the clean metal surface and also to surface coated by protective coatings as Plastizol, Tlumex etc.

ENVIRONMENT

The preparation must not be used for filling places which are in direct contact with food and drinking water.

APPLICATION

The surface must be clean and dry before application. Places, which are not intended to be treated by the preparation, must be covered. The preparation is supplied in consistence suitable for usage. Content in the can must be shaken well before usage. It is applied in distance from 20 to 30 cm. At temperature 20°C the preparation is dry after 4 hours.

UPPER COATINGS

Non-over paintable

TOOLS CLEANING

Dirty parts of tools can be cleaned with thinner S6006. Only non-hardened preparation can be cleaned.

STORAGE AND PACKAGING

It is necessary to ensure the temperature from +5 °C to 25°C and avoid direct solar radiation during storage and transport. Store in dry and cold place. We guarantee shelf life and quality of the product for 24 months.

Packaging:

- 500 ml – spray

COLOUR

Black

BKP GROUP, a. s.