

PolyKar[®] ZÁKLAD NA PLASTY

Primer for plastic parts, category : Fillers

DESCRIPTION AND USAGE

PolyKar ZÁKLAD NA PLASTY is one-component primer on plastic parts of car bodies. It dries very fast and is easy workable. It is excellent base for all common used spray coatings and paint systems including putties intended for car body repairs. It ensures especially high adhesion of upper coatings to plastics. It is not recommended for spraying of polyethylene and polypropylene.

ENVIRONMENT

PolyKar ZÁKLAD NA PLASTY must not be used for filling places which are in direct contact with food and drinking water.

APPLICATION

It is applied in 2 layers. Each layer must be leaved to draught about 5 – 10 minutes. Temperature of surface should be among 18 – 25°C. Do not thin!

Working viscosity: 4/20°C. circa 11-12 s

Nozzle of spray gun: Ø 1,3 - 1.5mm

Air pressure: 0,3 - 0,4 MPa

Thickness of dry layer is 20 µm

DRYING TIME

The preparation can be coated after 20 minutes at temperature 20°C. Drying time can be extended at temperatures lower than 20°C (minimally 17°C) and shortened at higher temperatures.

TOOLS CLEANING

Na PolyKar ZÁKLAD NA PLASTY lze použít všechny běžné nátěrové systémy.

STORAGE AND PACKAGING

It is necessary to ensure the temperature from 20°C and avoid direct solar radiation during storage and transport. Store in dry and cold place. We guarantee shelf life and quality of the product for 24 months.

Packaging:

- 1 l – a can

COLOUR

Transparent, white transparent

BKP GROUP, a. s.