

P o l y K a r[®] PUR HMOTA

Sealing compound, category : Special putties

DESCRIPTION AND USAGE

PolyKar PUR HMOTA is one-component polyurethane sealing compound with very good adhesion to metals (both raw and primed), then to stainless steel, aluminium, glass, concrete and most plastics. It is used for sealing of welded metal sheets of a car body. After hardening it remains elastic and can be lacquered with all types of car lacquers.

ENVIRONMENT

Mass must not be used for filling places which are in direct contact with food and drinking water.

APPLICATION

PolyKar PUR HMOTA must be applied on absolutely clean, dry and ungreased surface only. We recommend degrease the surface, then roughen with sanding paper and degrease again with PolyKar ODMAŠŤOVAČ. PolyKar PUR HMOTA is applicable by brush.

DRYING

The mass is dry till 5 – 7 minutes at temperature 20°C. 2 mm thick layer is absolutely hardened after 24 hours.

TOOLS CLEANING

Dirty parts of tools for filling can be cleaned with acryl thinner. Only non-hardened mass can be cleaned.

STORAGE AND PACKAGING

It is necessary to ensure the temperature from +5°C to + 25°C and avoid direct solar radiation during storage and transport. We guarantee shelf life and quality of the product for 12 months.

Packaging:

- 310 ml – a cartouche
- 0,85 kg – a can

COLOUR

white, gray, black

BKP GROUP, a. s.