

PolyKar[®] BITUMEN

Non-overpaintable protective coating, category : Protective coatings

DESCRIPTION AND USAGE

PolyKar BITUMEN, preparation for protection of car chassis, semi-trailers, ships and metal products, is made on the base of rubber and asphalt. It forms resistant elastic layer protecting against the abrasive treatment of spreadings, corrosion, petrol, oils, water and salt. Its function is also the sound protection. It has excellent adhesion to the clean metal surface and also to surface coated by protective coatings as Plastizol, Tlumex etc.

ENVIRONMENT

The preparation must not be used for filling places which are in direct contact with food and drinking water.

APPLICATION

The surface must be clean and dry before application. Places, which are not intended to be treated by the preparation, must be covered. The preparation is supplied in consistence suitable for usage. In case of need the preparation can be thinned with thinner S 6006.

PolyKar BITUMEN is applied by brush or by spray gun (best with high pressure non-air equipment)

It is applied in 2 or 3 layers, it is necessary to wait 5 minutes between application of each layer. At temperature 20°C the preparation is dry after 4 hours.

1 liter of preparation covers about 3,5 m² in thickness of layer 100 µm.

Content in the can must be shaken well before usage!!!

UPPER COATINGS

Non-overpaintable

TOOLS CLEANING**STORAGE AND PACKAGING**

Dirty parts of tools can be cleaned with thinner S6006. Only non-hardened preparation can be cleaned.

COLOUR

Black

BKP GROUP, a. s.